

| ROTAX [®] ENGINE | 900 ACE |
|---------------------------|-------------------------------------|
| Engine details | Liquid-cooled, four-stroke D.O.H.C. |
| Cylinders | 3 |
| Displacement | 899.0 cc |
| Bore | 74 mm |
| Stroke | 69.7 mm |
| Maximum engine speed | 7250 RPM |
| Carburation | EFI |
| Recommended fuel type | Unleaded |
| Minimum octane | 95 |
| Fuel tank | 42 liters |
| | |

COLOUR

White/Orange/Black

DIMENSIONS

| Vehicle overall length* | 3240 mm |
|-------------------------|----------|
| Vehicle overall width | 1200 mm |
| Vehicle overall height | 1500 mm |
| Ski stance | 996 mm |
| Track nominal width | 600 mm |
| Track nominal length | 3923 mm |
| Track profile height | 38 mm |
| flack profile fleight | 56 11111 |

POWERTRAIN

| Gearbox | 2F/N/R with push-button reverse |
|--------------------|---|
| Drive clutch type | pDrive with slider shoes |
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

SUSPENSION

| Front suspension | LFS with bended lower A-Arms |
|------------------|------------------------------------|
| Front shock | HPG 36 |
| Rear suspension | EasyRide with adjustment |
| Center shock | HPG 36 |
| Rear shock | HPG 36 |

FEATURES

| Frame | Radien-X |
|-----------------------|---|
| Skis | Blade DS+ |
| Seating | Modular, 1-up heated |
| Handlebar | U-type steel with hooks, low grab handle |
| Riser block height | 145 mm |
| Starter | Electric |
| Reverse | Electromechanical |
| Heated throttle lever | Standard |

| Heated grips | Standard |
|-------------------------|---------------------------------|
| Gauge | 4.5-in. digital display |
| Mirrors | Standard |
| Windshield | Extra high with side deflectors |
| Hitch | Standard |
| Visor Plug front / rear | Front |
| USB power outlet | Front |
| Air radiator with fan | Yes |
| LinQ attachment | Multi-LinQ plate |
| | |