

ROTAX® ENGINE	900 ACE Turbo	900 ACE Turbo R
Engine details	Liquid-cooled, four- stroke D.O.H.C., turbocharged	Liquid-cooled, four- stroke D.O.H.C., turbocharged
Cylinders	3	3
Displacement	899.0 cc	899.0 cc
Bore	74 mm	74 mm
Stroke	69.7 mm	69.7 mm
Maximum engine speed	7750 RPM	7900 RPM
Carburation	EFI	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	42	iters

COLOUR	White/Orange/Black	
DIMENSIONS		
Vehicle overall length*	3240 mm	
Vehicle overall width	1200 mm	
Vehicle overall height	1500 mm	
Ski stance	996 mm	
Track nominal width	600 mm	
Track nominal length	3923 mm	
Track profile height	38 mm	
mack prome neight	30 11111	

## **POWERTRAIN**

Gearbox	2F/N/R with push-button reverse	
Drive clutch type	pDrive	
Driven clutch type	QRS	
Hydraulic brake with braided steel braided s		

## **SUSPENSION**

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide with adjustment
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien-X	
Skis	Blade DS+	
Seating	Modular, 1+1	
Handlebar	U-type steel with hooks, low grab handle	
Riser block height	145 mm	
Starter	Electric	
Reverse	Electromechanical	
Heated throttle lever	Standard	

Heated grips	Standard	
Gauge	7.2-in. wide digital display	
Windshield	Extra high with side deflectors	
Hitch	Standard	
Visor Plug front / rear	Front	
USB power outlet	Front	
Air radiator with fan	Yes	
LinQ attachment	Multi-LinQ plate	

<sup>\*</sup> Vehicle overall length without snowflap.