

ROTAX® ENGINE	600R E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72,3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3,4 liters

COLOUR	Viper Red / Black
DIMENSIONS	
Vehicle overall length*	3250 mm
Vehicle overall width	1120 mm
Vehicle overall height	1290 mm
Ski stance	921 mm
Track nominal width	400 mm
Track nominal length	3912 mm
Track profile height	64 mm PowderMax Light

## **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## **SUSPENSION**

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS <sup>2</sup> -DS+ -3900
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien DS
Skis	Blade DS+
Seating	Shredder, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	145 mm
Starter	Manual Electric (spring only)

Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5-in. digital display
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs

<sup>\*</sup> Vehicle overall length without snowflap.