

ROTAX [®] ENGINE	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two- stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	849 cc	849 cc
Bore	82 mm	82 mm
Stroke	80.4 mm	80.4 mm
Maximum engine speed	7900 RPM	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3,4 liters	

COLOUR

Platinum Silver Satin / Viper Red

DIMENSIONS

Vehicle overall length*	3230 mm (3900) 3340 mm (4100)
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Frack nominal width	381 mm
Frack nominal length	3912 mm 4178 mm
Frack profile height	76 mm PowderMax Light Large 64 mm PowderMax Light (spring only 3900)

POWERTRAIN

5

Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, plastic master cylinder w protector	

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 Kashima
Rear suspension	PPS ² -DS+ -3900 PPS ² -DS+ -4100 (spring only)
Center shock	KYB 36 Kashima
Rear shock	KYB 36 Kashima

FEATURES

Frame	Radien ²	
Skis	Blade DS+	
Seating	Shredder DS, 1-up	
Handlebar	U-type aluminium with hooks, low grab handle	
Riser block height	120 mm	
Starter	Manual with SHOT	

RER
Standard
Standard
4.5-in. digital display 10.25-in Color Display with BRP Connect (spring only)
Yes, in front compartment
2 pairs