

ROTAX® ENGINE	600 EFI	600R E-TEC
Engine details	Liquid-cooled, two- stroke	Liquid-cooled, two- stroke, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	599.4 cc	599.4 cc
Bore	72.3 mm	72,3 mm
Stroke	73 mm	73 mm
Maximum engine speed	7500 RPM	8100 RPM
Carburation	EFI	Electronic Direct Injection
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3,4 liters	

COLOUR	Race Orange/Black
DIMENSIONS	
Vehicle overall length*	3160 mm (3700) 3270 mm (3900)
Vehicle overall width	1200 mm
Vehicle overall height	1250 mm
Ski stance	996 mm
Track nominal width	406 mm
Track nominal length	3705 mm 3923 mm
Track profile height	51 mm PowderMax

POWERTRAIN

Drive clutch type	pDrive with clickers (600R E-TEC) pDrive (600 EFI)	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

SUSPENSION

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS ² -DS+ -3700 PPS ² -DS+ -3900
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	145 mm
Starter	Electric and manual
Reverse	RER

Standard	
Standard	
4.5-in. digital display	
Low	
Front	
Yes, in front compartment	
2 pairs	

^{*} Vehicle overall length without snowflap.