## **EXPEDITION®** LE

A hybrid touring sport-utility vehicle with premium features for off-trail exploration and on-trail cruises.



**EXPEDITION LE** 900 ACE TURBO SHOWN

## // PACKAGE HIGHLIGHTS

- 20 in. wide Multi-LinQ® plate with 125 lb/56.7 kg cargo capacity
- $\bullet$  RAS  $^{\text{\tiny TM}}$  X crossover front suspension

// WHAT'S NEW

• Available with 20 in. or 24 in. track options

- $\bullet$  SC  $^{\dagger}$  -5U articulating rear suspension with locking mechanism (no tool required)
- Air radiator with fan
- Deep-snow running boards with large openings
- Removable passenger seat with heated grips
- Hitch receiver with 1,500 lb/680 kg towing capacity when equiped with an HD rear bumper. (1,200 lb/544 kg std.)
- · High-capacity battery
- Easy-shift transmission (H-L-N) with RER™ electronic reverse [2-stroke]/electro-mechanical reverse [4-stroke]
- 23 in. ultra-high windshield with side deflectors
- Pivoting mirrors
- Pilot™ 7.4 skis
- Heated driver's visor power outlet
- · Low handlebar strap
- pDrive™ clutch

ROTAX Engine	600R E-TEC	600R E-TEC 900 TUR		900 ACE Turbo	900 ACE
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged		Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower	125	180		130	95
Cylinders – Displacement	2 - 599.4 cc	3 - 899 cc		3 - 899 cc	3 - 899 cc
Bore – Stroke (mm)	72.3 – 73	73 - 69.7		73 - 69.7	73 – 69.7
Carburation	E-TEC direct injection	EFI		EFI	EFI
Fuel type – Octane	Premium unleaded - 91	Premium unleaded - 91		Premium unleaded - 91	Regular unleaded – 87
Fuel tank (L/US gal)	42/11.1	42/11.1		42/11.1	42/11.1
Oil tank capacity (L/qt)	3.4/3.6	3.3/3.5		3.3/3.5	3.3/3.5
POWERTRAIN Drive clutch	pDrive with clickers	pDrive		pDrive	pDrive
Driven clutch	, QRS Vent	QRS Vent		QRS Vent	QRS
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.		73 mm/2.86 in.	73 mm/2.86 in.
DRY WEIGHT					
Dry weight 20 in. track	617 lb	670 lb		666 lb	640 lb
Dry weight 24 in. track	626 lb	681 lb		676 lb	650 lb
DIMENSIONS			SUSPEN	SION	
Overall vehicle length	3,256 mm/128.2 in.		Front suspension		RAS X
Overall vehicle width	1,200 to 1,240 mm/47.7 to 48.8 in.		Front shock		HPG <sup>†</sup>
Overall vehicle height	1,513 mm/59.6 in.		Front suspension		220 mm/8.7 in.
Ski stance	1,000 mm/39 in. adjustable		travel		
Track	Silent Cobra WT:		Rear suspension		SC-5U
[Length x Width x Profile]	154 x 20 x 1.5 in.		Center shock		HPG
	154 x 24 x 1.5 in.		Rear shock		HPG
			Rear susper	sion travel	239 mm/9.4 in.

Arctic Desert / Black					
Black Black					
FEATURES					
Platform	REV® Gen4				
Skis	Pilot 7.4				
Seating	2-up modular with underseat storage				
Handlebar	Standard with J-hooks/Grab handle				
Riser block height	145 mm/5.7 in.				
Starter	Electric				
Reverse	RER (600R E-TEC) Electro-mechanic (ACE engines)				
Air radiator	High-efficiency w/ fan (4-stroke) Fan (2-stroke)				
Brake system	Brembo <sup>†</sup>				
Heated throttle lever/grips	Standard (driver and passenger)				
Gauge type	4.5 in. digital display				
Windshield	585 mm/23 in. with mirrors				
Runner – Carbide	Square 3/8 in 4 in				
Bumpers (front/ rear)	Heavy-duty/Hitch receiver				