## **EXPEDITION® SPORT**



## // WHAT'S NEW

• Three Rotax® engines available: 900 ACE™, 600 ACE and 600 EFI

COLOR

- // PACKAGE HIGHLIGHTS
- RAS™ X crossover front suspension
- $\, \cdot \, SC^{\dagger} 5U$  articulating rear suspension with locking mechanism (no tool required)
- Brembo† brake

- 420W magneto available with Rotax® ACE engines
- Heavy duty rear bumper with tongue-type hitch
- Air radiator with fan and engine oil cooler
- 2-up seat with removable LinQ® passenger backrest and handholds
- Deep-snow running boards with large openings

**EXPEDITION SPORT** 900 ACE SHOWN

- Standard with 2 sets of LinQ attachment points
- Adjustable ski stance
- Pilot™ DS 2 skis

ROTAX ENGINE	600 EFI	900 ACE	600 ACE
Engine details	Liquid-cooled,	Liquid-cooled,	Liquid-cooled,
	two-stroke	four-stroke D.O.H.C.,	four-stroke D.O.H.C.,
		dry sump	dry sump
Horsepower	85	95	62
Cylinders – Displacement	2 - 599.4 cc	3 - 899 cc	2 - 600.0 cc
Bore - Stroke (mm)	72.3 – 73	73 - 69.7	73 - 69.7
Carburation	EFI	EFI	EFI
Fuel type – Octane	Regular unleaded – 87	Regular unleaded - 87	Regular unleaded - 87
Fuel tank (L/US gal)	36/9.5	36/9.5	36/9.5
Oil tank capacity (L/qt)	3.4/3.6	3.3/3.5	2.1/2.2
POWERTRAIN			
Drive clutch	pDrive	pDrive	eDrive™ 2
Driven clutch	QRS	QRS	QRS
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	73 mm/2.86 in.
DRY WEIGHT			
Dry weight	504 lb	578 lb	532 lb
DIMENSIONS			
Overall vehicle length	3,309 mm/130.3 in.		
Overall vehicle width	1,140 to 1,180 mm/44.9 to 46.5 in.		
Overall vehicle height	1,513 mm/59.6 in.		
Ski stance	1,000 mm/39 in. adjustable		
Track	Charger:		
(Length x Width x Profile)	154 x 16 x 1.5 in.		

Black / Neo Yellow		
SUSPENSION		
Front suspension	RAS X	
Front shock	Motion Control	
Front suspension travel	210 mm/8.3 in.	
Rear suspension	SC-5U	
Center shock	Motion Control	
Rear shock	HPG <sup>†</sup>	
Rear suspension travel	239 mm/9.4 in.	
FFATURES		
FEATURES Platform	REV® Gen4	
Skis	Pilot DS 2	
Seating	2-up	
Handlebar	Standard with J-hooks	
Riser block height	145 mm/5.7 in.	
Starter	Electric	
Reverse	RER™ (600 EFI)	
	Mechanical	
	(ACE engines)	
Air radiator	Fan (4-stroke only)	
Brake system	Brembo	
Heated throttle lever/grips	Standard (driver only)	
Gauge type	4.5 in. digital display	
Windshield	585 mm/23 in.	
Runner – Carbide	Square 3/8 in. – 4 in.	
Bumpers (front/rear)	Std/Heavy Duty with tongue-type hitch	