

# RENEGADE® X®

High-performance and high-tech features for the most demanding rider.



RENEGADE X  
600R E-TEC SHOWN



RENEGADE X  
850 E-TEC SHOWN

## // WHAT'S NEW

- REV® Gen5 platform (850 E-TEC® only)
- 10.25" color touchscreen display with BRP Connect available (850 E-TEC only)
- Premium LED headlights

## // PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC on REV Gen5 platform
- Rotax® 600R E-TEC and 900 ACE™ Turbo R available
- High-performance shock package
- 7.8 in. wide LCD display with BRP Connect available (900 ACE Turbo R)
- RAS™ X front suspension
- rMotion™ X rear suspension
- Electric starter
- pDrive™ clutch
- Forward adjustable riser
- Transparent handguards
- Backlit multifunction handlebar controls

ROTAX ENGINE	850 E-TEC	600R E-TEC	900 ACE TURBO R
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Horsepower	165	125	180
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc	3 - 899 cc
Bore - Stroke (mm)	82 - 80.4	72.3 - 73	73 - 69.7
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection	EFI
Fuel type - Octane	Premium unleaded - 91	Premium unleaded - 91	Premium unleaded - 91
Fuel tank (L/US gal)	36/9.5	36/9.5	36/9.5
Oil tank capacity (L/qt)	3.4/3.6	3.4/3.6	3.3/3.5

### POWERTRAIN

Drive clutch	pDrive with clickers	pDrive with clickers	pDrive
Driven clutch	QRS Vent	QRS	QRS Vent
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	73 mm/2.86 in.


### DRY WEIGHT

Dry weight	486 lb	470 lb	524 lb
------------	--------	--------	--------

### DIMENSIONS

Overall vehicle length	3,038 mm/119.6 in.
Overall vehicle width	1,209 - 1,232 - 1,255 mm/47.6 - 48.5 - 49.4 in.
Overall vehicle height	1,267 mm/49.9 in.
Ski stance	1,090 mm / 43 in. adjustable
Track (Length x Width x Profile)	RipSaw <sup>1</sup> : 137 x 15 x 1.25 in. Ice Ripper <sup>11</sup> XT: 137 x 15 x 1.25 in. 137 x 15 x 1.5 in.

### COLOR

Neo Yellow / Black 

Black 

### SUSPENSION

Front suspension	RAS X
Front shock	HPG <sup>1</sup> Plus
Front suspension travel	243 mm/9.6 in.
Rear suspension	rMotion X
Center shock	HPG Plus
Rear shock	KYB <sup>1</sup> Pro 36 EA-3 (REV Gen5) KYB Pro 36 EA (REV Gen4)
Rear suspension travel	292 mm/11.5 in.

### FEATURES

Platform	REV Gen5 (850 E-TEC only) REV Gen4
Skis	Pilot™ X
Seating	Trail performance (2-stroke engines) Trail with storage (4-stroke engines)
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	Adjustable-120 mm/4.7 in.
Starter	Electric
Reverse	RER™ (E-TEC engines) Electro-mechanic (ACE engines)
Brake system	Brembo <sup>1</sup>
Heated throttle lever/grips	Standard
Gauge type	7.2 in. digital
Windshield	360 mm/14 in.
Runner - Carbide	Round 7/16 - 4 in.
Bumpers (front/rear)	Std/Std