SUMMIT® NEO®

A brand new sled with compact ergonomics that gives riders of any age a less intimidating experience with a full-size fun factor.

// PACKAGE HIGHLIGHTS

- REV® Gen4 platform
- Compact ergonomics
- Rotax 600 EFI 40 engine
- RAS™ 3 front suspension
- Neo rear suspension
- Motion control shocks
- 146 x 14 x 1.6 Cobra † with FlexEdge † track
- Pilot™ DS 2 skis
- Electric start
- RER™ reverse
- pDrive™ clutch

// NEO+ PACKAGE

- Rotax® 600 EFI 55 engine
- HPG† Front shocks
- 146 x 15 x 1.75 Hurricane† with FlexEdge track
- Low mountain strap
- Handguards



SUMMIT NEO SHOWN



SUMMIT NEO+ SHOWN

ROTAX ENGINE	600 EFI - 55	600 EFI - 40	
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, two-stroke	
Horsepower	55	40	
Cylinders – Displacement	2 - 599.4 cc	2 - 599.4 cc	
Bore - Stroke (mm)	72.3 – 73	72.3 – 73	
Carburation	EFI	EFI	
Fuel type – Octane	Regular unleaded – 87	Regular unleaded – 87	
Fuel tank (L/US gal)	36/9.5	36/9.5	
Oil tank capacity (L/qt)	3.4/3.6	3.4/3.6	
POWERTRAIN			
Drive clutch	pDrive	pDrive	
Driven clutch	QRS Lite	QRS Lite	
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	
DRY WEIGHT			
Dry weight	430 lb (Neo+)	419 lb (Neo)	
DIMENSIONS			
Overall vehicle length	3,174 mm/125 in.		
Overall vehicle width	1,080 to 1,110 mm/42.5 to 43.7 in.		
Overall vehicle height	1,095 mm/43 in.		
Ski stance	864 mm/34 in. adjustable		
Track	Cobra with FlexEdge (Neo):		
(Length x Width x Profile)	146 x 14 x 1.35 in.		
	Hurricane with FlexEdge (Neo+):		
	146 x 15 x 1.75 in.		

COLOR

Neo Yellow / Catalyst Grey (Neo)	
Neo Yellow / Black (Neo+)	

CHEDENCION

SUSPENSION	
Front suspension	RAS 3
Front shock	Motion Control (Neo)/HPG (Neo+)
Front suspension travel	196 mm/7.7 in.
Rear suspension	Neo
Center shock	Torsion spring
Rear shock	Motion Control
Rear suspension travel	220 mm/8.7 in.

FEATURES

Platform	REV Gen4
Skis	Pilot DS 2
Seating	Deep-snow compact and lightweight
Handlebar	Narrow standard with J-hooks Grab handle (Neo+)
Riser block height	120 mm/4.7 in.
Starter	Electric
Reverse	RER
Brake system	Brembo [†]
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital
Windshield	Optional
Runner – Carbide	Square 3/8 in. (optional)
Bumpers (front/rear)	Std/Std