2022

EXPEDITION° SWT

A supreme deep-snow sport-utility vehicle with unrivaled flotation and an exemplary list of utility features.

// WHAT'S NEW

• High-quality HPG shock package



- Rotax® 900 ACE™ Turbo 150 and 900 ACE™ engines
- 24 in. wide Multi-LinQ plate with 56.7 kg cargo capacity
- 4.5-in. digital display
- RAS™ 3 front suspension
- SC[™]-5U articulating rear suspension with locking mechanism (no tool required)
- · Air radiator with fan

ROTAX®

ENGINE Engine details

Horsepower

Driven clutch

Cylinders - Displacement

- Deep-snow running boards with large openings
- Removable passenger seat with heated grips
- High passenger backrest
- High-capacity battery
- Easy-shift transmission (H-L-N) with electromechanical reverse
- 23 in. Ultra-high windshield with side deflectors

QRS 73 mm

- Pivotina mirrors
- Pilot 7.4 skis

- Heated driver's visor power outlet
- Low handlebar strap
- pDrive™ clutch
- RF D.E.S.S.™ key

900 ACE™	CO
Liquid-cooled,	Lav
four-stroke D.O.H.C.,	_
dry sump	- su
95	
3 - 899 cc	Fro
73 mm – 69.7 mm	Fro
EFI	Fro

cymiacic biopiacomeni	0 000 00	0 000 00
Bore – Stroke	73 mm - 69.7 mm	73 mm – 69.7 mm
Carburation	EFI	EFI
Fuel type – Octane	Unleaded – 95	Unleaded – 95
Fuel tank	42 L	42 L
Oil tank capacity	3.3 L	3.3 L
POWERTRAIN		
Drive clutch	n∏rive™	nNrive™ with slider shoes

900 ACE™ TURBO - 150

Liquid-cooled,

four-stroke D.O.H.C.,

dry sump, turbocharged

150

3 - 899 cc

Drive sprocket pitch	/3 mm
DIMENSIONS	

22		
Overall vehicle length	3,256 mm	
Overall vehicle width	1,200 to 1,240 mm	
Overall vehicle height	1,656 mm	
Ski stance	975 or 1,020 mm	
Track	Silent Cobra WT:	
(Length x Width x Profile)	154 x 24 x 1.5 in.	

QRS Vent

OLOR

Lava Red / Black		
SUSPENSION		
Front suspension	RAS™ 3	
Front shock	HPG™	
Front suspension travel	220 mm	
Rear suspension	SC™-5U	
Center shock	HPG™	

HPG™

239 mm

FEATURES

Rear suspension travel

Rear shock

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	2-up modular with underseat storage
Handlebar	U-shaped aluminum with J-hooks/ Low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electro-mechanic
Air radiator	High-efficiency w/ fan
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard (driver and passenger)
Gauge type	4.5 in. digital display
Windshield	585 mm
Runner – Carbide	Square 3/8 in. – 4 in.
Bumpers (front/rear)	Heavy Duty/Hitch





EXPEDITION® SWT 900 ACE™ TURBO SHOWN